	Application No.	Applicant(s)	
Notice of Allowability	10/506 750	HOA ET AL	
	10/596,750 <b>Examiner</b>	HOA ET AL.  Art Unit	
	MIOLIAEL LEEELV	1704	
	MICHAEL J. FEELY	1761	
The MAILING DATE of this communication appears All claims being allowable, PROSECUTION ON THE MERITS IS herewith (or previously mailed), a Notice of Allowance (PTOL-85) NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIOF of the Office or upon petition by the applicant. See 37 CFR 1.313	(OR REMAINS) CLOSED in or other appropriate community. This application is s	this application. If not included inication will be mailed in due cou	rse. <b>THIS</b>
1. $\blacksquare$ This communication is responsive to <u>the RCE filed 12/14/20</u>	<u>)11</u> .		
<ol> <li>An election was made by the applicant in response to a rest the restriction requirement and election have been incorporate</li> </ol>		during the interview on;	
3. X The allowed claim(s) is/are 1,3-13,20,21,23,24,26,27 and 3.	<u>3-37</u> .		
<ul> <li>4. ☐ Acknowledgment is made of a claim for foreign priority unde</li> <li>a) ☐ All b) ☐ Some* c) ☐ None of the:</li> </ul>	er 35 U.S.C. § 119(a)-(d) or (	f).	
1.   Certified copies of the priority documents have	been received.		
2.   Certified copies of the priority documents have	been received in Applicatio	n No	
3. Copies of the certified copies of the priority do	cuments have been received	d in this national stage application	from the
International Bureau (PCT Rule 17.2(a)).			
* Certified copies not received:			
Applicant has THREE MONTHS FROM THE "MAILING DATE" noted below. Failure to timely comply will result in ABANDONM THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.		a reply complying with the require	ements
5. A SUBSTITUTE OATH OR DECLARATION must be submit INFORMAL PATENT APPLICATION (PTO-152) which give			CE OF
6. CORRECTED DRAWINGS ( as "replacement sheets") must	t be submitted.		
(a) including changes required by the Notice of Draftspers	on's Patent Drawing Review	v (PTO-948) attached	
1) 🔲 hereto or 2) 🔲 to Paper No./Mail Date			
(b) ☐ including changes required by the attached Examiner's Paper No./Mail Date	s Amendment / Comment or	in the Office action of	
Identifying indicia such as the application number (see 37 CFR 1 each sheet. Replacement sheet(s) should be labeled as such in t			ck) of
<ol> <li>DEPOSIT OF and/or INFORMATION about the deposit of B attached Examiner's comment regarding REQUIREMENT FO</li> </ol>			
Attachment(s)	- <b>-</b>		
1. Notice of References Cited (PTO-892)		formal Patent Application	
2. Notice of Draftperson's Patent Drawing Review (PTO-948)		ummary (PTO-413), Mail Date <u>20120312</u> .	
3. Information Disclosure Statements (PTO/SB/08), Paper No./Mail Date		Amendment/Comment	
Examiner's Comment Regarding Requirement for Deposit of Biological Material	8. 🗌 Examiner's	8.   Examiner's Statement of Reasons for Allowance	
• · · · · · · · · · · · · · · · · · · ·	9. ⊠ Other <u>Detai</u>	led Allowance.	
/MICHAEL J FEELY/			
Primary Examiner, Art Unit 1761			

Application/Control Number: 10/596,750 Page 2

Art Unit: 1761

### **EXAMINER'S AMENDMENT**

An examiner's amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.

Authorization for this examiner's amendment was given in a telephone interview with Michael P. Byrne (Reg. No. 54,015) on March 12, 2012.

The application has been amended as follows:

# *In the claims*:

- 1. (Currently Amended) A method for making a modified epoxy, comprising the steps of:
- a) preparing a clay solution comprising solvents, clay particles of a dimension in the nanometer range and agglomerates of clay particles;
- b) generating a flow of clay solution and submitting said flow to: (1) high pressure to generate high velocity and to allow shearing in the clay solution to occur; (2) a region of obstacles allowing the agglomerates of clay particles to be broken down; and (3) a sudden lower pressure, yielding a dispersed clay solution having a fine and homogeneous distribution of clay particles of a dimension in the nanometer range in the clay solution; and
- c) mixing the dispersed clay solution with at least a pristine epoxy, wherein a rubber material is optionally provided with the pristine epoxy during mixing.

### 2. (Cancelled)

- 3. (Currently Amended) The method according to claim 1, wherein said step a) comprises incorporating a first part of the pristine epoxy into the clay solution; and said step c) comprises mixing the dispersed clay solution with a remaining part of the pristine epoxy.
- 4. (Original) The method according to claim 1, wherein said step a) comprises mixing with at least one of mechanical and ultrasonic mixing.
- 5. (Original) The method according to claim 1, wherein said step b) comprises submitting the clay solution to a pressure of about 20,000 psi in tubes of a diameter of about 0.1 mm.
- 6. (Original) The method according to claim 1, wherein said step b) comprises exfoliating the clay particles in the solution.
- 7. (Previously Presented) The method according to claim 1, wherein said step c) comprises adding curing agents to yield a solid epoxy material.
- 8. (Currently Amended) The method according to claim 1, whereby the modified epoxy comprises agglomerates of less than about 1  $\mu$ m and agglomerates of a maximum diameter between about 1  $\mu$ m and 2  $\mu$ m.

9. (Previously Presented) The method according to claim 1, whereby the modified epoxy has

enhanced viscoelastic properties and improved fracture toughness compared to the pristine

epoxy.

10. (Currently Amended) The method according to claim 9, wherein a content of about 1 wt% of

clay loading and no optional rubber yields an increase in critical stress intensity (K<sub>1C</sub>) and critical

strain energy release rate  $(G_{1C})$  of 2 and 3 times respectively, with respect to the pristine epoxy.

11. (Original) The method according to claim 1, whereby the modified epoxy has enhanced

barrier properties, including water absorption resistance, adhesion strength and flammability

resistance, with respect to the pristine epoxy.

12. (Original) The method according to claim 1, wherein a mixture of clay and epoxy obtained

has a stability over an extended period of time.

13. (Original) The method according to claim 1, wherein the optional rubber is provided with the

pristine epoxy during mixing.

14 - 19. (Cancelled)

20. (Currently Amended) A modified epoxy produced from a pristine epoxy, the modified epoxy

having at least higher barrier properties and thermal resistance, a higher critical stress intensity

factor  $(K_{1C})$ , and a higher critical strain energy release rate  $(G_{1C})$  than the pristine epoxy, the modified epoxy produced by:

- a) preparing a clay solution comprising solvents, clay particles of a dimension in the nanometer range and agglomerates of clay particles;
- b) generating a flow of clay solution and submitting said flow to: (1) high pressure; (2) high velocity and breaking impacts in a region of obstacles to allow the agglomerates to be broken down; and (3) a sudden lower pressure, yielding a dispersed clay solution having a fine and homogeneous distribution of clay particles of a dimension in the nanometer range in the clay solution; and
- c) mixing the dispersed clay solution with at least part of the pristine epoxy, wherein a rubber material is optionally provided with the pristine epoxy during mixing;

wherein a content of about 1wt% of clay loading and no optional rubber yields an increase in  $K_{1C}$  and  $G_{1C}$  of 2 and 3 times respectively, with respect to the pristine epoxy.

- 21. (Original) The modified epoxy according to claim 20, comprising finely dispersed clay agglomerates of less than about 1  $\mu$ m and agglomerates of a maximum diameter between about 1  $\mu$ m and 2  $\mu$ m.
- 22. (Cancelled)
- 23. (Previously Presented) The modified epoxy according to claim 21, wherein the optional rubber is provided with the pristine epoxy during mixing.

Application/Control Number: 10/596,750 Page 6

Art Unit: 1761

24. (Original) The modified epoxy according to claim 21, further comprising additives.

25. (Cancelled)

26. (Currently Amended) The modified epoxy according to claim 23, wherein the optional

rubber is CTBN, and a content of 6 phr of clay loading and 20 phr of CTBN yields an increase in

 $K_{1C}$  and  $G_{1C}$  of 2.2 and 7.6 times respectively, with respect to the pristine epoxy.

27. (Currently Amended) The method according to claim 13, wherein the optional rubber is

CTBN, and a content of 6 phr of clay loading and 20 phr of CTBN yields an increase in critical

stress intensity factor ( $K_{1C}$ ) and critical strain energy release rate ( $G_{1C}$ ) of 2.2 and 7.6 times

respectively, with respect to the pristine epoxy.

28 - 32. (Cancelled)

33. (Currently Amended) A modified epoxy produced from a pristine epoxy, the modified epoxy

having at least a higher flammability resistance and a higher fracture toughness than the pristine

epoxy, the modified epoxy produced by:

a) preparing a clay solution comprising solvents, clay particles of a dimension in the

nanometer range and agglomerates of clay particles;

- b) generating a flow of clay solution and submitting said flow to: (1) high pressure; (2) high velocity and breaking impacts in a region of obstacles to allow the agglomerates to be broken down; and (3) a sudden lower pressure, yielding a dispersed clay solution having a fine and homogeneous distribution of clay particles of a dimension in the nanometer range in the clay solution; and
- c) mixing the dispersed clay solution with at least part of the pristine epoxy; wherein a content of 6 phr of clay loading yields an increase in critical strain energy release rate ( $G_{1C}$ ) of 5.8 times, with respect to the pristine epoxy.
- 34. (Currently Amended) The modified epoxy of claim 33, wherein said step c) comprises adding curing agents to yield a solid epoxy material.
- 35. (Currently Amended) A modified epoxy produced from a rubber-modified pristine epoxy, the modified epoxy having at least a higher flammability resistance and a higher fracture toughness than the rubber-modified pristine epoxy, the modified epoxy produced by:
- a) preparing a clay solution comprising solvents, clay particles of a dimension in the nanometer range and agglomerates of clay particles;
- b) generating a flow of clay solution and submitting said flow to: (1) high pressure; (2) high velocity and breaking impacts in a region of obstacles to allow the agglomerates to be broken down; and (3) a sudden lower pressure, yielding a dispersed clay solution having a fine and homogeneous distribution of clay particles of a dimension in the nanometer range in the clay solution; and

Application/Control Number: 10/596,750

Art Unit: 1761

Page 8

c) mixing the dispersed clay solution with at least part of the rubber-modified pristine

epoxy;

wherein the rubber of the rubber-modified pristine epoxy is CTBN, and a content of 6 phr

of clay loading and 20 phr of CTBN yields an increase in critical strain energy release rate (G<sub>1C</sub>)

of 7.6 times, with respect to the pristine epoxy.

36. (Previously Presented) The modified epoxy of claim 35, wherein said step c) comprises

adding curing agents to yield a solid epoxy material.

37. (Previously Presented) The modified epoxy of claim 20, wherein said step c) comprises

adding curing agents to yield a solid epoxy material.

#### **DETAILED ALLOWANCE**

## **Pending Claims**

Claims 1, 3-13, 20, 21, 23, 24, 26, 27, and 33-37 are pending.

### Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on December 14, 2011 has been entered.

#### Election/Restrictions

2. Previously submitted claims 28-32 (Group II) were directed to an invention that was independent or distinct from the invention originally claimed. Since applicant received an action on the merits for the originally presented invention, this invention was constructively elected by original presentation for prosecution on the merits. Accordingly, claims 28-32 were withdrawn from consideration as being directed to a non-elected invention. See 37 CFR 1.142(b) and MPEP § 821.03. Claims 28-32 are now cancelled.

Application/Control Number: 10/596,750 Page 10

Art Unit: 1761

## Response to Amendment

3. The rejection of claims 20, 21, and 24 under 35 U.S.C. 102(e) as anticipated by or, in the alternative, under 35 U.S.C. 103(a) as obvious over Chen et al. (XP008051803) has been overcome by amendment.

4. The rejection of claim 23 under 35 U.S.C. 103(a) as being unpatentable over Chen et al. (XP008051803) in view of Furihata (US Pat. No. 4,465,542) has been overcome by amendment.

## Allowable Subject Matter

5. Claims 1, 3-13, 20, 21, 23, 24, 26, 27, and 33-37 are allowed.

Communication

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to MICHAEL J. FEELY whose telephone number is (571)272-

1086. The examiner can normally be reached on M-F 8:30 to 5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Harold Y. Pyon can be reached on 571-272-1498. The fax phone number for the

organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would

like assistance from a USPTO Customer Service Representative or access to the automated

information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/MICHAEL J FEELY/

Primary Examiner, Art Unit 1761

March 14, 2012